



Safety data sheet for AIREX[®] C71

According to 2001/58/EG

Page 1 of 3

revised: 16.09.2009

1.	Identification of substance / preparation and of the company				
	AIREX [®] C71 Rigid foam				
	(C71.55, C71.75)				
	Use of substance / preparation : Core material in sandwich constructions				
	Company identification:	Alcan Airex AG			
		CH-5643 Sins (Switzerland)			
		Phone +41 41 789 66 00			
		Fax +41 41 789 66 60			
2.	Composition / Information on ingredients				
	Rigid polymeric foam on the basis of Polyvinylchloride modified by an interpenetrating polymer network with aromatic amides.				
	Blowing agent: Carbon dioxide (CO2 / produced by the reaction of water with isocyanate components).				
	Further ingredients: Residues of chemical blowing agent. Organic colour pigments. Stabilisers.				
3.	Hazards identification				
	AIREX [®] C71 does not constitute any risk to public health and environment if it is used as intended.				
	Possible health issues:				
	- Harmful to health due to inhaling vapour and dust that may be produced by sawing, grinding and thermoforming.				
	- Harmful to health due to ingesting dust that may be produced by grinding and sawing.				
4.	First aid measures				
	Inhalation of processing fumes: Move victim to fresh air; obtain medical attention if irritation persists.				
	Inhalation of gases in case of fire: Move victim to fresh air and obtain medical attention.				
	Skin contact: Wash with water.				
	Eye contact: Flush with water if irritation develops.				
	Ingestion: No special measures required. Seek medical attention if symptoms develop.				
5.	Fire-fighting measures				
	Suitable extinguishing media: foam, water spray, extinguishing powder, carbon dioxide.				
	Extinguishing media which must not be used: direct water jet.				
	Hazardous combustion products: hydrogen chloride (HCI) and hydrogen cyanide (HCN).				
	Use respiratory protection independent of recirculated air.				
6.	Accidental release measures				
	No special measures require	ed.			
7.	Handling and storage				
	Handling: It must be ensured that there is good ventilation and suction on the processing machines and where dust develop- ment may occur.				
	Storage: Stow away from immediate and dangerous sources of ignition. Danger of electrostatic charges when stored in very dry areas.				





Safety data sheet for AIREX[®] C71

According to 2001/58/EG

Page 2 of 3

revised: 16.09.2009

8. Exposure control / personal protection

General protection measures

Sufficient air circulation is required during processing. The exhaust air must not be recirculated. If the workstation cannot be sufficiently ventilated, it is imperative that respiratory protection (A2P3 filter) is worn.

Workstation threshold values

Dust	Source	Value type	Value (mg/m ³)	Remarks
	SUVA	MAC values	10	Inhalable particles

	Gasses / V	√apours	Source	Value type	Value (mg/m ³)	Remarks		
	Tetramethylsuccinonitrile		SUVA	MAC values	3			
	MethacryInitrile		SUVA	MAC values	3			
	Personal p	Personal protection equipment						
	Res	piratory protection:	effective breathin	fective breathing mask				
	Hand protection: glo		gloves	gloves				
	Eye protection:		goggles					
9.	Physical and chemical properties							
	-	tate / form:	Polymer foam sheet with visible cell structure.					
	Colour: various, depending on density.							
			65 to 80 °C ISO 537					
	Decomposition temperature		> 220 °C					
	Flash ignition temperature		380 °C	ASTM D 1929				
	0	30 - 350 kg/m ³	ISO 845					
	Density	0		, acida alkalia aliah	otio budro corbono			
	Solubility	Insoluble in		r, acids, alkalis, aliph		_		
		Soluble in	Aromatic hydroca	arbons, Ketones, chi	orinated hydrocarbons	S		
10.	Stability and reactivity							
	General information: Stable under normal conditions							
	Conditions to avoid: high temperatures (> 180 °C)							
	Materials to avoid: not applicable.							
	Dangerous decomposition products: Tetramethylsuccinonitrile (TMSN) Methacrylnitrile Isobutyronitrile Hydrogen chloride (HCl) Hydrogen cyanide (HCN) in small amounts Carbon monoxide (CO) Cothen dioxide (CO)							

Carbon dioxide (CO₂)





Safety data sheet for AIREX[®] C71

According to 2001/58/EG

Page 3 of 3

revised: 16.09.2009

11.	Toxicological information						
	Toxicological tests: No data available.						
	Experience with man:						
	Skin contact: Grinding dust may cause irritation to people with sensitive skin.						
	Eye contact: Dust may cause irritation.						
	Inhalation: Dust may cause irritation of respiration tract. Dizziness, nausea and headaches may occur if processing (sawing, grinding or tempering) is performed without sufficient ventilation and respiratory protection over several hours in small, poorly ventilated areas.						
	Ingestion: No symptoms known.						
12.	Ecological information						
	Ecotoxicity: The total amount of all heavy metals is <100 mg/kg [ppm].						
	Mobility: Not soluble in water, therefore effects on groundwater are unlikely.						
	Persistence and degradability. Biologically not degradable.						
13.	Disposal considerations						
	Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.						
14.	Transport information						
	Railroad	RID	no restriction				
	Road	ADR	no restriction				
	Sea	IMDG Code	no restriction				
	Air	ICAO-TI/IATA-DGR	no restriction				
	UN-Classificati	ion	not required				
15.	Regulatory information						
	AIREX [®] C71 rigid plastic foam does not require marking under the dangerous substances and preparation directives 67/548/EWG and 1999/45/EG.						
16.	Other information						
	This issue of the safety data sheet replaces the issue released on 27.05.2003.						
	The information given in this material safety data sheet is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.						