

Safety data sheet for AIREX® R82

According to Regulation (EC) No. 1907/2006 & GHS Page 1 of 3 revised: January 23rd, 2017

GM--SDS-014

1. Identification of substance / preparation and of the company

AIREX® R82 Rigid foam (R82.60, R82.80, R82.110)

Use of substance / preparation : Core material in sandwich constructions

Company identification: Airex AG

5643 Sins, Switzerland Tel +41 41 789 66 00 Fax +41 41 789 66 60

2. Hazards identification

AIREX® R82 does not constitute any risk to public health and environment if it is used as intended.

Fine dust is produced while sawing, milling, grinding and sanding.

Irritant fumes may be produced while thermoforming.

3. Composition / Information on ingredients

Rigid polymeric foam on the basis of Polyetherimide (PEI), foamed using non ozone depleting blowing agents.

Further ingredients: Residual solvents (< 1%) (non halogenated organic solvents).

4. First aid measures

Inhalation of processing fumes: Move victim to fresh air; obtain medical attention if irritation persists.

Inhalation of gases in case of fire: Move victim to fresh air and obtain medical attention.

Skin contact: Wash with water.

Eye contact: Flush with water if irritation develops.

Ingestion: No special measures required. Seek medical attention if symptoms develop.

5. Fire-fighting measures

Suitable extinguishing media: Foam, water spray, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used: Direct water jet.

Hazardous combustion products: Carbon monoxide (CO).

6. Accidental release measures

No special measures required.

7. Handling and storage

Handling: No special measures required.

Storage: Stow away from immediate and dangerous sources of ignition. Danger of electrostatic

charges when stored in very dry areas.

8. Exposure control / personal protection

Exposure limit values: Not applicable.

Exposure controls: The use of gloves, protective goggles and dust masks and also the use of dust extraction

equipment is recommended for sawing, milling, grinding and sanding. For thermoforming, the workplace should be continuously supplied with fresh air. Where necessary, a

respiratory protection is recommended.

www.3ACcorematerials.com

T +86 21 585 86 006 | F +86 21 338 27 298 corematerials.asia@3AComposites.com



Safety data sheet for AIREX® R82

According to Regulation (EC) No. 1907/2006 & GHS Page 2 of 3 revised: January 23rd, 2017

GM--SDS-014

9. Physical and chemical properties

Physical state / form: Polymer foam sheet with visible cell structure.

Colour: White.

Glass transition temperature: approx. 190 °C ISO 537

Decomposition temperature > 482 °C

Flash ignition temperature 587 °C ASTM D 1929

Density: 50 - 130 kg/m³ ISO 845

Solubility: Insoluble in: Water, sea water, acids, alkalis, aliphatic hydrocarbons, alcohols, carbon tetrachloride,

ether

Soluble in: Dichloromethane, triichloromethane, N-methyl-2-pyrrolidone, dimethyl sulfoxide,

low molecular weight resins at elevated temperature.

10. Stability and reactivity

General information: Stable under normal conditions

Conditions to avoid: Not applicable

Materials to avoid: Not applicable

Dangerous decomposition products: Nitrous oxides (

osition products: Nitrous oxides (NO_x)
Carbon monoxide (CO)

Carbon dioxide (CO₂)

11. Toxicological information

Toxicological tests: No data available.

Experience with man:

Skin contact: Does not contain any materials which are known to stimulate allergic reactions.

Grinding dust may cause irritation to people with sensitive skin.

Eye contact: Dust may cause irritation.

Inhalation: Dust may cause irritation of respiration tract.

Ingestion: No symptoms known.

12. Ecological information

Ecotoxicity: The total amount of all heavy metals is <100 mg/kg [ppm].

Mobility: Not soluble in water, therefore effects on groundwater are unlikely.

Persistence and degradability: Biologically not degradable.

13. Disposal considerations

Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.

14. Transport information

Railroad RID No restriction.

Road ADR No restriction.

Sea IMDG Code No restriction.

Air ICAO-TI/IATA-DGR No restriction.

UN-Classification Not required.



Safety data sheet for AIREX® R82

According to Regulation (EC) No. 1907/2006 & GHS

Page 3 of 3

revised: January 23rd, 2017 GM--SDS-014

15. Regulatory information

AIREX® R82 rigid plastic foam rigid plastic foam does not require marking under the following directives or is not concerned by the following regulations:

- Europe: Directive 67/548/EWG, ("DSD"), Directive 1999/45/EC, ("DPD"), Regulation (EC) No 1272/2008 ("CLP").
- US: OSHA .29 CFR 1910.1200 and .49 CFR 171.8 (EPA 40 CFR 117) spill, leak and disposal regulations of the US Department of Transportation.
- Canada: WHMIS and TDG.

16. Other information

This issue of the safety data sheet replaces the issue released on July 22nd, 2016.

The information given in this material safety data sheet is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.