

Certificate No: **TAK00007K** Revision No:

# TYPE APPROVAL CERTIFICATE

This is to certify:

That the Glass Fibre Products

with type designation(s)

Uni-axial: (0°) (200-2000 g/m²) with and without chopped strand mats (100-500 g/m²), Uni-axial: (90°) (250-1900 g/m²) with and without chopped strand mats (100-500 g/m²)

Issued to

# Telateks Tekstil Urunleri Sanayi Ve Ticaret A.S. (METYX Composites)

Tuzla, Istanbul, Turkey

is found to comply with

DNV GL rules for classification - High speed and light craft

DNV GL class programme DNVGL-CP-0467 – Type approval – Uni- and multi-axial multi-ply fabrics made of glass fibres

Det Norske Veritas Standards' for Certification No. 2.21, Craft, 2010

Det Norske Veritas' Standards for Certification No. 2.20, Lifeboats and Rescue Boats, 2007

### **Application:**

For use in marine vessels according to stated Rules/Standards.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Issued at <b>Høvik</b> on <b>2021-01-21</b>	
This Certificate is valid until <b>2026-01-20</b> .	for <b>DNV GL</b>
DNV GL local station: <b>Istanbul</b>	
Approval Engineer: <b>Gisle Hersvik</b>	
	Gustav Heiberg
	Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2020-02 www.dnvgl.com Page 1 of

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-011606-9** Certificate No: **TAK000007K** 

Revision No: 1

# **Product description**

#### **METYX® Glass Fibre Reinforcements:**

Uni-axial: (L)  $0^{\circ}$  (200-2000 g/m<sup>2</sup>) with and without (M) (100-500 g/m<sup>2</sup>) Uni-axial: (T)  $90^{\circ}$  (250-1900 g/m<sup>2</sup>) with and without (M) (100-500 g/m<sup>2</sup>)

The following properties have been verified by Type Testing of laminates:

Property - Orientation	Test Method	L 600	L 1000			
Tensile Strength - Longitudinal	ISO 527	457	434	msmv	MPa	
Tensile Modulus - Longitudinal	ISO 527	27 389	28 994	msv	MPa	
Tensile Elongation - Longitudinal	ISO 527	3.7	4.2	msmv	%	
Glass content	ISO 1172	53.0	52.8	mean	%	
Flexural Strength - Longitudinal	ISO 14125	806	823	msmv	MPa	
Flexural Modulus - Longitudinal	ISO 14125	25 211	24 250	msv	MPa	
Flexural Elongation - Longitudinal	ISO 14125	3.6	4.6	msmv	mm	
Glass content	ISO 1172	52.9	53.3	mean	%	
Resin	CE 266 N12 ISO Polyester					
Curing Procedure for Type Testing	24 hrs at room temperature, post-cured 3 hrs at 80°C					

#### Legends:

msmv = Manufacturer's Specified Minimum Value, verified to be below mean - 2 x standard deviation of Type Test results

msv = Manufacturer's Specified Value, verified to be within  $\pm$  10% of mean of Type Test results.

*mean* = Mean of Type Test results

L: Longitudinal

T: Transverse

M: Chopped Strand Mat

#### **Application/Limitation**

Manufacture of FRP components for applications including marine vessels - and rotor blades within wind energy (ref. DNVGL-ST-0376).

The approval covers the weight ranges stated above.

Any significant changes in design and / or quality of the material will render the approval invalid.

# Type Approval documentation

#### **Tests carried out**

Type Testing carried out in accordance with **Type Approval documentation**.

# Marking of product

Product shall be marked with *manufacturer's name*: **Telateks Tekstil Urunleri San. ve A.S. (Metyx®), Tuzla / Istanbul, Turkey** and *type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

Form code: TA 251 Revision: 2020-02 www.dnvgl.com Page 2 of 3

Job Id: **262.1-011606-9** Certificate No: **TAK000007K** 

Revision No: 1

# **Periodical assessment**

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention and Certificate Renewal) shall be performed according to DNVGL-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <a href="https://approvalfinder.dnvgl.com">https://approvalfinder.dnvgl.com</a>

END OF CERTIFICATE

Form code: TA 251 Revision: 2020-02 www.dnvgl.com Page 3 of 3