



TYPE APPROVAL CERTIFICATE

Certificate No:
TAK00000R5
Revision No:
1

This is to certify:

That the Glass Fibre Products

with type designation(s)
Glass Woven (200-1800 g/m²) with and without chopped strand mats (50-600 g/m²)

Issued to

Telateks Tekstil Urunleri Sanayi Ve Ticaret A.S.
(METYX Composites)
Tuzla, Istanbul, Türkiye

is found to comply with

DNV class programme DNV-CP-0467 – Type approval – Uni- and multi-axial multi-ply fabrics made of glass fibres
DNV rules for classification – High speed and light craft
DNV standard DNV-ST-0342 – Craft

Application :

For use in marine vessels according to stated Rules/Standards.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Høvik** on **2022-12-21**

This Certificate is valid until **2027-12-20**.

DNV local unit: **Istanbul**

Approval Engineer: **Gisle Hersvik**

for **DNV**

Gustav Heiberg
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

METYX® Glass Fibre Reinforcements.

Glass Woven (200-1800 g/m²) with or without CSM (50-600 g/m²)
 - Plain woven

Legends:

G: Glass

W: Woven

CSM: Chopped Strand Mat

The following indicative properties have been verified by Type Testing of laminates:

| Property | Test Method | GW600 | | |
|-----------------------------------|--|-----------|-----|-----------|
| Tensile Strength – 0° | ISO 527-4 | 389 | MPa | msmv |
| Tensile Modulus – 0° | ISO 527-4 | 35 | GPa | msv |
| Tensile Elongation – 0° | ISO 527-4 | 1.3 / 1.2 | % | mean/msmv |
| Flexural Strength | ISO 14125 | 476 | MPa | msmv |
| Flexural Modulus | ISO 14125 | 20 | GPa | msv |
| Fibre content (by weight) | - | 39 | % | mean |
| Resin | Scott Bader Crystic VE676-03 Vinyl Ester Resin | | | |
| Curing Procedure for Type Testing | 24 hrs at room temperature, 3 hrs at 80°C | | | |

Legends:

msmv = Manufacturer's Specified Minimum Value (verified to be below mean - 2 standard deviation of Type Test results)

msv = Manufacturer's Specified Value

mean = Mean of Type Test results

Application/Limitation

The approval covers the weight ranges stated above.

Any significant changes in design and / or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out according to **Type Approval documentation**.

Marking of product

Product shall be marked with *manufacturer's name*: **Telateks Tekstil Urunleri Sanayi Ve Ticaret A.S. (METYX Composites), Tuzla / Istanbul, Turkey** and *type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE