

A2200 Release Film

A2200 is a low cost, very flexible release film which is ideal for resin infusion processing.

Coloured opaque orange to allow resin front to be monitored during infusion plus aiding complete removal whilst de bagging.

Suitable for use with epoxy, polyester and vinylester resins although we strongly advise that a test piece is produced prior to committing to a full scale infusion in order to determine compatibility and performance meet desired standards.

PHYSICAL PROPERTIES

, m. olonia i ilonia ilonia	Value	Method
- Material	PE	
- Maximum Use Temperature	120°C	
- Colour	Orange	
- Elongation at break	500% ±10%	ASTM D882
- Density	0.9g/cm ³	ASTM D1505

AVAILABILITY AND PACKAGING

- Standard thickness	25μ
- Standard perforation	P31 (See details on the perforations data sheet)
- Standard widths	0.1m, 1.30m and 1.45m
	(Other sizes and thicknesses on request)

STORAGE AND HANDLING

Store in its original packaging.

No shelf life limitation.

No skin irritation problems experienced.

AEROVAC SYSTEMES FRANCE

AEROVAC SYSTEMS LIMITED

AEROVAC SYSTEMS ITALY S.r.I

RICHMOND AIRCRAFT PRODUCTS
www.richmondaircraft.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.