

AEROFIX3

Spray adhesive

Ideally suited to bonding applications

Features

- A repositionable, high strength adhesive spray compatible with gelcoat, barrier-coat, glass fibre matting and fiberglass laminates.
- Fully compatible with polyester and vinylester resins.
- Does not compromise the mechanical performance of laminates, even used in higher quantities than actually required.
- Does not compromise or inhibit the correct polymerisation of resins.
- Does not weaken the degree of interlaminar adhesion between the different layers of a laminate.
- Contains a blue colourant which makes it possible to assess and regulate the quantity of Aerofix 3 applied, with the colour disappearing during polymerisation.

Instructions for use

- Shake the aerosol well before use and ensure that the surfaces to be bonded are clean and dry.
- Hold the aerosol vertically and spray an even layer of adhesive from a distance of 25cm (10in). It must not have the appearance of being wet. If this is the case, spray from a little further away.
- To achieve optimum adhesion, spray the adhesive onto both surfaces to be joined and wait around one minute so that the solvent present in the adhesive may evaporate.
- Finally, press the two surfaces firmly together to ensure good adhesion takes place.
- After each use, purge the aerosol by holding it upside down.

Availability

Contents: 500ml/1pint, but also available in larger quantities upon request.

Storage

- If the product is stored in the dark in its original, perfectly sealed container at a maximum temperature of 20°C (68°F), it will remain stable for at least 12 months from the date of production. If stored outside these conditions, the shelf life cannot be guaranteed. Storage for longer periods, or in conditions other than those specified, can alter the characteristics of the product, in some cases making it unusable.
- Aerofix 3 is supplied in a pressurised container. Protect from direct sunlight and do not expose to temperatures of more than 50°C (122°F).

Health & safety

Do not use near heat sources or functioning electronic appliances.

No skin irritation problems experienced.

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.