

LTS90B/G Sealant tape



Tel: +44 (0) 1274 550500
Fax: +44 (0) 1274 550501
Email: sales@aerovac.com
Website: www.aerovac.com

- Economic, low cost vacuum bag sealant tape suitable for ambient, de-bulk and medium temperature applications.
- Widely used in the wind, marine and glass industries.
- Excellent tack.
- Also suitable for high temperature envelope bagging applications.
- Material compatible with most substrates (including composite tools) and film materials.
- For optimum results, tape must be allowed to cool to an ambient temperature before stripping from mould surfaces.

PHYSICAL PROPERTIES

- Maximum use temperature
Up to 150°C bag to tool
Up to 180°C bag to bag
- Colour
Black (LTS90B)
Grey (LTS90G)

AVAILABILITY & PACKAGING

- Roll size
15m x 12mm x 3mm
(also available as a 4mm diameter bead)
- Standard box contents
22 rolls
50 boxes per pallet

STORAGE & HANDLING

- Must be stored in its original containers, under optimum conditions of between 5 and 25°C.
- Material has a two year shelf life from date of manufacture.
- Must be stored flat.
- Boxes should not be stacked more than 5 high.
- Handling of these products must conform to individual company guidelines and health and safety regulations.

Aerovac Systems Ltd www.aerovac.com	Aerovac Systems Italy S.r.l www.aerovac.it	Aerovac Systèmes France www.aerovac.fr	Richmond Aircraft Products www.richmondaircraft.com
-----------------------------------------------------------------------------	-----------------------------------------------------------------------------------	-------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------

Aerovac Systems Ltd.

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith. All values stated are nominal. For further details about tolerances please contact Aerovac Systems quality department.

Revised: February 2010