

AIOO, AIOOPS, AIOOFLOGREEN Nylon Release Fabric

- Porous nylon release fabric
- Heat set and scoured - can be used directly against laminates or bond lines
- No need to clean surface where secondary bonding, painting or finishing is required
- Imparts a relatively coarse weave pattern upon removal from the laminate
- Releases from most commercial resin systems
- Available with a red tracer line spaced every 30mm and in fluorescent green for ease of identification on the cured laminate. Designation for this product is A100PS (Pin Striped) and A100Flogreen (fluorescent green)
- A comprehensive selection of slit widths is available from stock

Note: Due to natural affinity between phenols and nylons this material is not recommended for use with phenolic resin or prepreg or used at temperatures higher than 180°C.

PHYSICAL PROPERTIES

- | | |
|------------------------------|---|
| • Maximum Cure Temperature | 180°C |
| • Fabric Thickness (nominal) | 0.145mm |
| • Fabric Weight (nominal) | 80g/m ² |
| • Colour | Natural (White)
Pin Striped
Fluorescent Green |

AVAILABILITY & PACKAGING

- | | |
|-------------|-------------------|
| • Roll size | 100m x 1.52m wide |
|-------------|-------------------|

STORAGE & HANDLING

- No special storage conditions required

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.