

LE Tape

Silicone or Acrylic Adhesive

- General purpose, high modulus PTFE tape
- Excellent release and temperature resistance
- Ideal for many applications including:- temporary tool surface repairs, sealing of split moulds to prevent resin penetration and where localised tool release in tight angles is required
- Acrylic adhesive also available
- Application very simple, due to the tape having no backing liner
- Strips easily after use

PHYSICAL PROPERTIES

• Maximum Use Temperature	Silicone Adhesive - 230°C Acrylic Adhesive - 180°C
• Film Thickness (nominal)	0.05mm
• Adhesive Thickness	0.034mm
• Elongation	125%
• Adhesion	Silicone Adhesive 2.79 N/cm Acrylic Adhesive 3.91 N/cm
• Breaking Strength	Silicone Adhesive 45 N/cm Acrylic Adhesive 36 N/cm
• Colour	Brown

AVAILABILITY & PACKAGING

• Standard widths	25mm, 50mm & 76mm widths up to 350mm are available
• Roll length	33m

STORAGE & HANDLING

- No special requirements

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.

revision: May 2002