Revision Date 14/02/2013 Revision 8

Revision 8



SAFETY DATA SHEET CRYSTIC CRESTOMER 1196PA

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name CRYSTIC CRESTOMER 1196PA

Product No. OL1004

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier Scott Bader

Wollaston Wellingborough

Northamptonshire. NN29 7RL Tel: +44(0)1933 663100

Emergency (24 hours) +44(0)1933 663399

Fax: +44(0)1933 663693 E-mail: reach@scottbader.com

1.4. Emergency telephone number

National Emergency Telephone Number +44(0)1933 663399

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Liq. 3 - H226

Human health Acute Tox. 4 - H312;Acute Tox. 4 - H332;Skin Irrit. 2 - H315;Eye Irrit. 2 -

H319;Skin Sens. 1 - H317;Repr. 2 - H361d;STOT SE 3 - H335;STOT RE 2 -

H373

Environment Aquatic Chronic 3 - H412

Classification (1999/45/EEC) Xn;R20/21, R48/20. Repr. Cat. 3;R63. Xi;R36/37/38. R43. R10, R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Vapours/aerosol spray may irritate the respiratory system. Risk of sensitisation or allergic reactions among sensitive individuals. Suspected of damaging fertility. Suspected of damaging the unborn child.

Physical and Chemical Hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

2.2. Label elements

Contains 2-HYDROXYETHYL ACRYLATE

STYRENE

Label In Accordance With (EC) No. 1272/2008



Signal Word Warning

Hazard Statements

H2	226	Flammable liquid and vapour.
H3	312	Harmful in contact with skin.
H3	315	Causes skin irritation.
H3	317	May cause an allergic skin reaction.
H3	319	Causes serious eye irritation.
H3	332	Harmful if inhaled.
H3	335	May cause respiratory irritation.
H3	861d	Suspected of damaging the unborn child.
H3	373	May cause damage to organs through prolonged or repeated exposure.
H4	112	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

313 Get medical advice/attention.

Supplementary Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.
P260 Do not breathe vapour/spray.
P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.
P321 Specific treatment (see medical advice on this label).

P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for

extinction.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P308+313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.
P322 Specific measures (see ... on this label).

P332+313 If skin irritation occurs: Get medical advice/attention.
P333+313 If skin irritation or rash occurs: Get medical advice/attention.

P337 If eye irritation persists:

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P403+235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to ...

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

OKTOTIO OKESTOMEK TISOLA						
2-HYDROXYETHYL ACRYLATE			<0.4%			
CAS-No.: 818-61-1	EC No.: 212-454-9					
Classification (FC 1272/2009)		Classification (C7/E40/EEC)				
Classification (EC 1272/2008) Acute Tox. 3 - H311		Classification (67/548/EEC) T;R24				
Skin Corr. 1B - H314		C;R34				
Skin Sens. 1 - H317		R43				
Aquatic Acute 1 - H400		N;R50				
COBALT(II) 2-ETHYLHEXANOATE			<0.3%			
CAS-No.: 136-52-7	EC No.: 205-250-6					
Classification (EC 1272/2008)		Classification (67/548/EEC)				
Acute Tox. 4 - H302		Xn;R22.				
Skin Sens. 1 - H317		Repr. Cat. 3;R62.				
Repr. 2 - H361f		N;R50/53.				
Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		R43.				
FUMED SILICIA (CAB-O-SIL)			4-6%			
TOWED SILION (CAB-O-SIL)			4-0 %			
CAS-No.: 112945-52-5	EC No.: 231-545-4					
Classification (EC 1272/2008)		Classification (67/548/EEC)				
Not classified.		Not classified.				
HYDROXYPROPYL METHACRYLATE			<0.4%			
CAS-No.: 27813-02-1	EC No.: 248-666-3					
Classification (EC 1272/2008)		Classification (67/548/EEC)				
Eye Irrit. 2 - H319		R43				
Skin Sens. 1 - H317		Xi;R36				
N,N-DIMETHYL-PARA-TOLUIDINE			<0.2%			
CAS-No.: 99-97-8	EC No.: 202-805-4					
Classification (EC 1272/2008)		Classification (67/548/EEC)				
Acute Tox. 3 - H301		T;R23/24/25				
Acute Tox. 3 - H311		R33				
Acute Tox. 3 - H331		R52/53				
STOT RE 2 - H373 Aquatic Chronic 3 - H412						
Solvent Naphtha (Petroleum), Light Arc	omatic (< 0,1% Benzene)		<0.2%			
CAS-No.: 64742-95-6	EC No.: 265-199-0					
Classification (EC 1272/2008)		Classification (67/548/EEC)				
Flam. Liq. 3 - H226		Xn;R65.				
EUH066		Xi;R37.				
STOT SE 3 - H335, H336		N;R51/53.				
Asp. Tox. 1 - H304		R10,R66,R67.				
Aquatic Chronic 2 - H411						

STYRENE 45-50%

CAS-No.: 100-42-5 EC No.: 202-851-5

Classification (EC 1272/2008)

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d Classification (67/548/EEC) Xn;R20,R48/20,R65. Repr. Cat. 3;R63. Xi;R36/37/38. R10.

Repr. 2 - H361d STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition Comments

Urethane Acrylate Resin in reactive solvent

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

Inhalation

Place unconscious person on the side in the recovery position and ensure breathing can take place. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

Skin contact

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL -	- 15 Min	Notes
FUMED SILICIA (CAB-O-SIL)	OEL	6 mg\m3	2.4 mg/m3			
		total dust	resp.dust			
STYRENE	WEL	100 ppm	430 mg/m3	250 ppm	1080 mg/m3	

OEL = Occupational Exposure Limit.

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

STYRENE (CAS: 100-42-5)

Ingredient Comments
WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment







Process conditions

Provide eyewash station.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

Respiratory equipment

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.
Colour Varying.
Odour Solvent.

Solubility Insoluble in water

Initial boiling point and boiling range 50-150

(°C)

Relative density 0.6 25°C

Flash point (°C) 25 CC (Closed cup).

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerisation

May polymerise.

10.4. Conditions to avoid

Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials To Avoid

Alkali metals. Strong oxidising substances. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Other Health Effects

Toxic to Reproductive Health Category 3.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

May cause sensitisation by skin contact.

Eye contact

Irritation of eyes and mucous membranes.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available.

12.4. Mobility in soil

Mobility:

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1866 UN No. (IMDG) 1866 UN No. (ICAO) 1866

14.2. UN proper shipping name

Proper Shipping Name RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3
IMDG Class 3
ICAO Class/Division 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user

EMS F-E, S-E
Emergency Action Code •3Y
Hazard No. (ADR) 30
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date 14/02/2013

Revision 8

Risk Phrases In Full

R34 Causes burns.

R33 Danger of cumulative effects.

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20 Harmful by inhalation. R22 Harmful if swallowed.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.
R63 Possible risk of harm to the unborn child.

R62 Possible risk of impaired fertility.

R66 Repeated exposure may cause skin dryness or cracking.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R24 Toxic in contact with skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R50 Very toxic to aquatic organisms.

Hazard Statements In Full

H319 Causes serious eye irritation.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H412 Harmful to aquatic life with long lasting effects.
H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H336 May cause drowsiness or dizziness.
H335 May cause respiratory irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H361f Suspected of damaging fertility.

H361d Suspected of damaging the unborn child.

H331 Toxic if inhaled.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.

H411 Toxic to aquatic life with long lasting effects.
H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.