Revision Date 18/02/2013 Revision 4

Revision 4



# SAFETY DATA SHEET CRYSTIC CRESTABOND M7-05 CARTRIDGE

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name CRYSTIC CRESTABOND M7-05 CARTRIDGE

Product No. OL1139

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

## 1.3. Details of the supplier of the safety data sheet

Supplier Scott Bader

Wollaston Wellingborough

Northamptonshire. NN29 7RL Tel: +44(0)1933 663100

Emergency (24 hours) +44(0)1933 663399

Fax: +44(0)1933 663693 E-mail: reach@scottbader.com Regulatory Affairs Manager

#### 1.4. Emergency telephone number

National Emergency Telephone Number

+44(0)1933 663399

Contact Person

# **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Liq. 2 - H225

Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317;STOT SE 3 - H335

Environment Aquatic Chronic 3 - H412

Classification (1999/45/EEC) Xi;R36/37/38. R43. F;R11. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Irritating to eyes and skin. Harmful by inhalation, in contact with skin and if swallowed.

Environment

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

# 2.2. Label elements

Contains METHYL METHACRYLATE

Label In Accordance With (EC) No. 1272/2008





Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention.

P501 Dispose of contents/container to ...

Supplementary Precautionary Statements

P313

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.
P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.
P321 Specific treatment (see medical advice on this label).

P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for

extinction.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332+313 If skin irritation occurs: Get medical advice/attention.
P333+313 If skin irritation or rash occurs: Get medical advice/attention.

P337 If eye irritation persists:

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P403+235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

# 2.3. Other hazards

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

BUTYLATED HYDROXY TOLUENE <0.4%

CAS-No.: 128-37-0 EC No.: 204-881-4

Classification (EC 1272/2008) Classification (67/548/EEC)

Aguatic Acute 1 - H400 N;R50/53.

Aquatic Chronic 1 - H410

CUMENE HYDROPEROXIDE <0.5%

CAS-No.: 80-15-9 EC No.: 201-254-7

 Classification (EC 1272/2008)
 Classification (67/548/EEC)

 Org. Perox. E - H242
 O;R7

 Acute Tox. 4 - H302
 T;R23

 Acute Tox. 3 - H312
 C;R34

 Acute Tox. 3 - H331
 Xn;R21/22,R48/20/22

 Skin Corr. 1B - H314
 N;R51/53

 STOT SE 3 - H335
 STOT RE 2 - H373

 Aquatic Chronic 2 - H411
 Aquatic Chronic 2 - H411

 DIPROPYLENE GLYCOL DIBENZOATE
 4-6%

 CAS-No.: 27138-31-4
 EC No.: 248-258-5

 Classification (EC 1272/2008)
 Classification (67/548/EEC)

METHACRYLIC ACID 2-4%

N:R51/53.

CAS-No.: 79-41-4 EC No.: 201-204-4

Classification (EC 1272/2008)

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Skin Corr. 1A - H314

STOT SE 3 - H335

METHYL METHACRYLATE 50-55%

CAS-No.: 80-62-6 EC No.: 201-297-1

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition Comments

Aquatic Chronic 2 - H411

Urethane Acrylate Resin in reactive solvent

## **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

Inhalation

Place unconscious person on the side in the recovery position and ensure breathing can take place. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

Skin contact

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention if any discomfort continues. Eye contact

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Do not use water jet as an extinguisher, as this will spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases

#### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 6.4. Reference to other sections

# **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

# 7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

Storage Class

Flammable liquid storage.

# 7.3. Specific end use(s)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
METHACRYLIC ACID	WEL	20 ppm	72 mg/m3	40 ppm	143 mg/m3	
METHYL METHACRYLATE	WEL	50 ppm	208 mg/m3	100 ppm	416 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

# CRYSTIC CRESTABOND M7-05 CARTRIDGE METHYL METHACRYLATE (CAS: 80-62-6)

Ingredient Comments
WEL = Workplace Exposure Limits

# 8.2. Exposure controls

Protective equipment





Process conditions

Provide eyewash station.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

Respiratory equipment

Wear mask supplied with: Gas cartridge suitable for organic substances.

Hand protection

Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Appearance Paste Colour White.

Odour Strong. Acrylic.

Solubility Insoluble in water

Flash point (°C) 10 CC (Closed cup).

# 9.2. Other information

#### **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

## 10.2. Chemical stability

Stable under normal temperature conditions.

# 10.3. Possibility of hazardous reactions

Hazardous Polymerisation

May polymerize.

# 10.4. Conditions to avoid

Avoid exposure to high temperatures or direct sunlight.

# 10.5. Incompatible materials

Materials To Avoid

Alkali metals. Strong oxidising substances. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

## 10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

Toxicological information

No information available.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Harmful by inhalation.

Inaestion

Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Harmful in contact with skin. Risk of sensitisation or allergic reactions among sensitive individuals.

Eye contact

Causes burns. Extreme irritation of eyes and mucous membranes, including burning and tearing.

#### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** 

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

## 12.2. Persistence and degradability

# 12.3. Bioaccumulative potential

## 12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

## **SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

#### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

#### **SECTION 14: TRANSPORT INFORMATION**

## 14.1. UN number

UN No. (ADR/RID/ADN) UN1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133

# 14.2. UN proper shipping name

Proper Shipping Name ADHESIVES

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3
IMDG Class 3
ICAO Class/Division 3

Transport Labels



## 14.4. Packing group

ADR/RID/ADN Packing group II
IMDG Packing group II
ICAO Packing group II

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

## 14.6. Special precautions for user

EMS F-E, S-D
Emergency Action Code •3YE
Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## 15.2. Chemical Safety Assessment

## **SECTION 16: OTHER INFORMATION**

Revision Date 18/02/2013

Revision 4

Risk Phrases In Full

R34 Causes burns.
R35 Causes severe burns.

R21/22 Harmful in contact with skin and if swallowed.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R11 Highly flammable

R36/37/38 Irritating to eyes, respiratory system and skin.
R37/38 Irritating to respiratory system and skin.

R37 Irritating to respiratory system.

R7 May cause fire.

R43 May cause sensitisation by skin contact.

R23 Toxic by inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H319 Causes serious eye irritation.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H412 Harmful to aquatic life with long lasting effects.

H242 Heating may cause a fire.

H225 Highly flammable liquid and vapour.H317 May cause an allergic skin reaction.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H335 May cause respiratory irritation.

H331 Toxic if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.